

Technical Data Sheet

MOTIONCOAT® HUV 4510

HUV curable gloss topcoating for use with MotionCoat® varnish

Product Description

MotionCoat® HUV 4510 is applied overall, through the anilox/blanket coater, over the pattern applied with Motioncoat® HUV 45 Litho Primer.

General Information		
Product Type	Coatings	
Product Technology	HUV curing	
Field Of Application	Paperbased Packaging, Publication & Commercial, Advertising, Catalogs, Commercial, Decorative packaging, exterior, Folded Boxes-Household/Hardware & Electronics/other non food, Folded Boxes-Personal Care/Cosmetics, Folded Boxes:Spirits/Wine, Other non-food, Other Specialities, Shelf-ready packaging, Transport packaging	
Properties	Chemical resistance, Enables an even and structured surface, Good printability, good adhesion, Suitable for the two-sided coating, The coating contains optical brightener.	
Optic	Glossy	

Properties

Gloss	00000000
Reactivity	00000000
Scuff Resistance	00000000
Slip Surface Smoothness	00000000
Flexibility	00000000
Hot Foil Stamping	00000000
Two Sided Coating	00000000
UV Varnishing	00000000
Counter Glueing	00000000

Product Characteristics				
Viscosity	• ~275 mPas +/- 50 (Centipoise at 25°C)			
Curing	• 150 fpm @ 300WPI HUV lamp			
Hot Foil Stamping	No	Glueability	Yes	
Anti Penetration	No			



Technical Data Sheet

MOTIONCOAT® HUV 4510

HUV curable gloss topcoating for use with MotionCoat® varnish

Substrate Recommendation

- Coated Board
- Coated Paper

Application Method

• Blanket, Flexo or Chambered Anilox Coaters, 10-14 bcm; Please refer to ACTEGA's usage guide for the set up and application techniques to create the best Motioncoat effects in combination with the Motioncoat first down varnish.

Storage Instructions

- Shelf-life 6 months
- Applies to closed original containers at 5°C up to 30°C.

Cleaning Instructions

• Please clean maschines and tools with commercial cleaning agents.

Additional Information

MEK Resistance: 20 - 40 Double Rubs
* Estimated chemical resistance on press

Contact Information

ACTEGA North America, Inc. 1450 Taylors Lane, Cinnaminson, NJ 08077 US +1 800-255-0021 info.ACTEGA@altana.com www.actega.com

Disclaimer

The characteristics contained herein constitute binding product specifications which we warrant provided the conditions and testing methods mentioned therein are used. Any other subjective or objective requirements concerning the products are excluded. Any information herein about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. No warranties of merchantability or fitness for a particular purpose are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties.