

Technical Data Sheet Starkote[®] AQ-17

Aqueous Matte Low Odor Coating

Product Description

Offline matte primer for offline UV coating; low odor

General Information			
Product Type	Coatings		
Product Technology	Water based		
Field Of Application	Paperbased Packaging, Publication & Commercial, Commercial, Advertising, Catalogs, Decorative packaging, exterior, Folded Boxes-Household/Hardware & Electronics/other non food, Folded Boxes-Personal Care/Cosmetics, Other non-food		
Properties	Good printability, good adhesion, Good wetting on different printing inks, e. g. conventional, UV printing inks, web offset printing inks, make tests!, Proves in practice to be suitable as coating for the later counter glueing., Suitable for the two-sided coating, Very suitable for hot foil stamping, Suitability of foils must be checked, An overcoating with UV varnishes and water based coatings is possible.		
Optic	Matte		

Properties

Gloss
Scuff Resistance
Slip Surface Smoothness
Hot Foil Stamping
Two Sided Coating
UV Varnishing
Counter Glueing

Product Characteristics				
Viscosity	• ~ s -1 (15-18) -2 (19-22) -3 (23-26) (#3 Zahn Cup at 23°C)			
Hot Foil Stamping	No	Glueability	No	
Drying AQ	Hot air knives with air evacuation	Slip Angle	24 +/- 2 Degrees	
Heat Resistance	140°F @ 16 hrs @ 2 PSI	Anti Penetration	No	



Technical Data Sheet Starkote® AO-17

Aqueous Matte Low Odor Coating

Substrate Recommendation

- Coated Board
- Coated Paper

Application Method

• Blanket, Tower, Dampener and Anilox Coaters, 9-11 bcm

Storage Instructions

- Shelf-life 6 months
- Applies to closed original containers at 5°C up to 30°C.
- Protect from frost, heat and sun exposure. Storage may cause a change in viscosity. We recommend to check the viscosity and adjust if necessary with water.

Cleaning Instructions

• Please clean machine and tools immediately with room temperature water or hot water. In cases where the coating has been left to dry, warm water and INKO Cleaner may be required.

Regulatory Compliance

• Disclaimer: For regulatory compliances please reach out to your responsible ACTEGA contact person.

Contact Information

ACTEGA North America, Inc. 1450 Taylors Lane, Cinnaminson, NJ 08077 US +1 800-255-0021 info.ACTEGA@altana.com www.actega.com

Disclaimer

The characteristics contained herein constitute binding product specifications which we warrant provided the conditions and testing methods mentioned therein are used. Any other subjective or objective requirements concerning the products are excluded. Any information herein about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. No warranties of merchantability or fitness for a particular purpose are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties.