

## Technical Data Sheet

### STARKOTE® AQ-586

Aqueous Gloss Ink Jet Receptive Coating

## Product Description

Aqueous gloss work & turn topcoat. Hot foil stampable and Ink Jet Receptive.

General Information	
Product Type	Coatings
Product Technology	Water based
Field Of Application	Publication & Commercial, Advertising, Brochures, Catalogs, Commercial, Displays, Other non-food
Properties	Good printability, good adhesion, Suitable for the two-sided coating, Proves in practice to be suitable as coating for the later counter glueing.
Optic	Glossy

## Properties

Gloss


Scuff Resistance

Slip Surface Smoothness

Hot Foil Stamping

Two Sided Coating

Counter Glueing



Product Characteristics			
Viscosity	• ~ s -1 (15-18) -2 (19-22) (#3 Zahn Cup at 23°C)		
Hot Foil Stamping	No	Glueability	No
Drying AQ	• Hot air knives with air evacuation	Slip Angle	20 +/- 2 degrees
Heat Resistance	150°F @ 16 hrs @ 2 PSI	Anti Penetration	No

## Substrate Recommendation

- Coated Board
- Coated Paper

## Application Method

- Blanket, Tower, Dampener and Anilox Coaters, 9-11 bcm

## Technical Data Sheet

### STARKOTE® AQ-586

Aqueous Gloss Ink Jet Receptive Coating

#### Storage Instructions

- Shelf-life 12 months
- Applies to closed original containers at 5°C up to 30°C.
- Protect from frost, heat and sun exposure. Storage may cause a change in viscosity. We recommend to check the viscosity and adjust - if necessary - with water.

#### Cleaning Instructions

- Please clean machine and tools immediately with room temperature water or hot water. In cases where the coating has been left to dry, warm water and INKO Cleaner may be required.

#### Contact Information

ACTEGA North America, Inc.

1450 Taylors Lane, Cinnaminson, NJ 08077 US

+1 800-255-0021

info.ACTEGA@altana.com

www.actega.com

#### Disclaimer

The characteristics contained herein constitute binding product specifications which we warrant provided the conditions and testing methods mentioned therein are used. Any other subjective or objective requirements concerning the products are excluded. Any information herein about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. No warranties of merchantability or fitness for a particular purpose are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties.