

Technical Data Sheet ULTRASHEEN® EB-7919 LMS

EB curable, low migration coating with high COF.


Product Description

EB curable, low migration coating with high COF.

General Information		
Product Type	Coatings	
Product Technology	UV Ebeam curing	
Field Of Application	Flexible Packaging, Paperbased Packaging, Decorative packaging, exterior, Dry foodstuff packagings, Folded Boxes-Confectionary, Other Portion Pack	
Properties	CoF, Good printability, good adhesion, Low odor, Proves in practice to be suitable as two-sided coating.	
Optic	Glossy	

Properties

Gloss Slip Surface Smoothness Flexibility Two Sided Coating Counter Glueing



Product Characteristics			
Viscosity	• ~150 mPas +/- 25 (Centipoise at 25°C)		
Curing	• 3 Mrad / 120KV / 200 ppm O2		
Hot Foil Stamping	No	Glueability	No
Slip Angle	COF: 0.35 Static	Anti Penetration	No

Substrate Recommendation

• Various films and paper

Printing Equipment and Anilox Recommendation	
Printing Equipment	Anilox Volume
Gravure or Flexo coater, 4-7 bcm anilox	- / - BCM



Technical Data Sheet ULTRASHEEN® EB-7919 LMS

EB curable, low migration coating with high COF.

Storage Instructions

- Shelf-life 6 months
- Applies to closed original containers at 5°C up to 30°C.

Cleaning Instructions

• Please clean maschines and tools with commercial cleaning agents.

Regulatory Compliance

• Disclaimer: For regulatory compliances please reach out to your responsible ACTEGA contact person.

Additional Information

MEK Resistance: 15 - 35 Double Rubs
* Estimated chemical resistance on press

Contact Information

ACTEGA North America, Inc. 1450 Taylors Lane, Cinnaminson, NJ 08077 US +1 800-255-0021 info.ACTEGA@altana.com www.actega.com

Disclaimer

The characteristics contained herein constitute binding product specifications which we warrant provided the conditions and testing methods mentioned therein are used. Any other subjective or objective requirements concerning the products are excluded. Any information herein about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. No warranties of merchantability or fitness for a particular purpose are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties.