

TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TERRAWET Matt Coating G 9/56 M FoodSafe-040

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Printing and reproduction of recorded media
Rolling
The product is intended for professional use.

Recommended restrictions
on use : For industrial use only.

1.3 Details of the supplier of the safety data sheet

Company : ACTEGA Terra GmbH
Industriestraße 12
31275 Lehrte

Telephone : +49513250090
Telefax : +4951325009110

E-mail address : qum.actega.terra@altana.com

1.4 Emergency telephone number

+44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 **H318: Causes serious eye damage.**

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : **Danger**

Hazard statements : **H318 Causes serious eye damage.**

Precautionary statements : **Prevention:**
P280 Wear eye protection/ face protection.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006


TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

- 577-11-7 docusate sodium

Additional Labelling

EUH208 Contains 1,2-Benzisothiazol-3-one, 2-methyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). **May produce an allergic reaction.**

2.3 Other hazards

Water-based products typically contain isothiazolinone biocides, including methyl isothiazolinone, as in-can preservatives. Such biocides may cause allergic skin reactions in already sensitised individuals.

May produce an allergic reaction.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Chemical nature : Waterbased polymerdispersion

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
docusate sodium	577-11-7 209-406-4 01-2119491296-29	Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 3 - < 5
Alcohols, C16-18, ethoxylated	68439-49-6	Acute Tox. 4; H302 Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 0,1 - < 0,25
1,2-Benzisothiazol-3-one	2634-33-5 220-120-9 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	< 0,05
2-methyl-2H-isothiazol-3-one	2682-20-4 220-239-6	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311	< 0,0015

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006


TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

	01-2120764690-50	Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0,0015
Substances with a workplace exposure limit :			
Silicon dioxide	7631-86-9 231-545-4 01-2119379499-16		>= 1 - < 3

SECTION 4: First aid measures
4.1 Description of first aid measures

- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with warm water.
Do not remove solidified product.
Call a physician if irritation develops or persists.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Skin contact may provoke the following symptoms:
Allergies

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SECTION 5: Firefighting measures
5.1 Extinguishing media

- Suitable extinguishing media : Water spray jet
Alcohol-resistant foam
Carbon dioxide (CO₂)
ABC powder

TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous decomposition products formed under fire conditions.
Do not allow run-off from fire fighting to enter drains or water courses.

5.3 Advice for firefighters

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Avoid subsoil penetration.
Do not flush into surface water or sanitary sewer system.
Retain and dispose of contaminated wash water.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Flush with water.
Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : The slight ammonia smell can become stronger if the product will be heated up higher than room temperature.
Provide sufficient air exchange and/or exhaust in work rooms.
For personal protection see section 8.

Hygiene measures : General industrial hygiene practice. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

7.2 Conditions for safe storage, including any incompatibilities

Advice on common storage : Keep in a dry, cool and well-ventilated place.
No special restrictions on storage with other products.

Recommended storage temperature : 5 - 35 °C

7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silicon dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m ³ (Silica)	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	2,4 mg/m ³ (Silica)	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

	industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.
	TWA (Respirable dust) 0,1 mg/m3 2004/37/EC
Further information	Carcinogens or mutagens

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
docusate sodium	Industrial use	Skin contact	Long-term systemic effects	31,3 mg/kg
	Industrial use	Inhalation	Long-term systemic effects	44,1 mg/m3
	Professional use	Skin contact	Long-term systemic effects	18,8 mg/kg
	Professional use	Inhalation	Long-term systemic effects	13 mg/m3
	Professional use	Ingestion	Long-term systemic effects	18,8 mg/kg
Silicon dioxide	Workers	Inhalation	Long-term systemic effects	4 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
docusate sodium	Fresh water	0,0066 mg/l
	Marine water	0,0007 mg/l
	Intermittent releases	0,066 mg/l
	Fresh water sediment	
	Soil	0,138 mg/kg
	Sewage treatment plant	122 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
 Break through time : 240 min
 Glove thickness : 0,4 mm
 Glove length : Gauntlets
 Directive : Equipment should conform to EN 374

Remarks : Preventive skin protection

Skin and body protection : Work uniform or laboratory coat.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

Respiratory protection	: No personal respiratory protective equipment normally required.
General advice	: Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Avoid subsoil penetration. Do not flush into surface water or sanitary sewer system. Retain and dispose of contaminated wash water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: dispersion
Colour	: milky, white - off-white
Odour	: slight, ammoniacal, acrylic-like
Odour Threshold	: No data available
pH	: 8,0 - 8,6 (20 °C)
Melting point/freezing point	: No data available
Boiling point/boiling range	: ca. 100 °C
Flash point	: Greater than 100 °C Method: ASTM D 93, Pensky-Martens closed cup Other information: Will not burn
Evaporation rate	: Not applicable
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: < 0,1 hPa similar to water
Relative vapour density	: No data available
Density	: ca. 1,05 g/cm ³ (20 °C) Method: DIN 53217
Solubility(ies) Water solubility	: completely miscible
Ignition temperature	: not auto-flammable
Flow time	: 35 - 50 s at 20 °C Cross section: 4 mm Method: DIN 53211

9.2 Other information

Metal corrosion rate	: Not applicable
----------------------	------------------

TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

Self-ignition : Method: No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : None reasonably foreseeable.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No decomposition if used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

docosate sodium:

Acute oral toxicity : LD50 (Rat, male and female): > 2.000 mg/kg
Method: OECD Test Guideline 401

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): 58,8 mg/l
Exposure time: 4 h
Method: OECD Test Guideline 403
GLP: yes

Skin corrosion/irritation

Product:

Remarks: May irritate skin.

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

Respiratory or skin sensitisation

Product:

Remarks: May cause sensitisation of susceptible persons by skin contact.

Germ cell mutagenicity

Product:

Germ cell mutagenicity- Assessment : Contains no ingredient listed as a mutagen

Carcinogenicity

Product:

Carcinogenicity - Assessment : Contains no ingredient listed as a carcinogen

Reproductive toxicity

Product:

Reproductive toxicity - Assessment : Contains no ingredient listed as toxic to reproduction

STOT - single exposure

Product:

Remarks: No data available

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Product:

No aspiration toxicity classification

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

docusate sodium:

Toxicity to fish : LC50 (Fish): 49 mg/l

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 6,6 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

aquatic invertebrates

Toxicity to algae : ErC50 (algae): 82,5 mg/l

Alcohols, C16-18, ethoxylated:

M-Factor (Short-term (acute) aquatic hazard) : 1

1,2-Benzisothiazol-3-one:

M-Factor (Short-term (acute) aquatic hazard) : 1

2-methyl-2H-isothiazol-3-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 6,0 mg/l
Exposure time: 96 h

LC50 (Lepomis macrochirus (Bluegill sunfish)): 12,4 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1,6 mg/l
Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata): 0,157 mg/l
Exposure time: 72 h

M-Factor (Short-term (acute) aquatic hazard) : 10

Toxicity to microorganisms : (Pseudomonas putida): 2,3 mg/l
Exposure time: 16 h

M-Factor (Long-term (chronic) aquatic hazard) : 1

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1):

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): 0,018 mg/l
Exposure time: 72 h

M-Factor (Short-term (acute) aquatic hazard) : 100

M-Factor (Long-term (chronic) aquatic hazard) : 100

12.2 Persistence and degradability

Product:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Biodegradation: < 50 %
Exposure time: 29 d
Method: OECD Test Guideline 301B
Remarks: According to the results of tests of biodegradability this product is not readily biodegradable.

Chemical Oxygen Demand : > 150.000 mg/l

(COD)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : Do not dispose of waste into sewer.
The product should not be allowed to enter drains, water courses or the soil.
Do not mix waste streams during collection.
If recycling is not practicable, dispose of in compliance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
The following Waste Codes are only suggestions:
waste paint and varnish containing organic solvents or other dangerous substances
waste ink containing hazardous substances

Contaminated packaging : Empty remaining contents.
Do not re-use empty containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information**14.1 UN number**

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

IMDG : Not regulated as a dangerous good
Remarks : IMDG Code segregation group - none

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0,51 %, 7,38 g/l
Remarks: VOC content excluding water

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information	:	This safety datasheet only contains information relating to safety and does not replace any product information or product specification. The evaluation of this mixture for the purpose of classification and labeling is based on calculations and bridging principles (essentially similar mixtures, batch analogy).
-------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TERRAWET Matt Coating G 9/56 M FoodSafe-040

Version 4.0 SDS_GB

Revision Date 13.08.2020

Print Date 14.08.2020

Sections, highlighted in grey, indicates changes towards the previous version.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.